

Safety Data Sheet

Aug. 13, 2015 page 1

| <p>1. Product and manufacturer Product name Type of product Company</p> <p>Application</p> | <p>HOT MELT GLUE STICKS JASCO PTY LTD 1-5 COMMERCIAL ROAD KINGSGROVE NSW 2208 AUSTRALIA PH: +61 02 98071555</p> <p>Hot melt sticks are glue which are environmentally friendly. They are used to glue gun and applied to many areas, such metal, wood, rope, etc.</p> | | | | | | | | | | |
|---|---|------------|---------|-------|--------|-----|--------|-----------|-------|--------|------|
| <p>2. Information of product composition</p> | <table style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: left;">Components</th> <th style="text-align: right;">% Range</th> </tr> </thead> <tbody> <tr> <td>RESIN</td> <td style="text-align: right;">20-45%</td> </tr> <tr> <td>EVA</td> <td style="text-align: right;">45-70%</td> </tr> <tr> <td>MICRO WAX</td> <td style="text-align: right;">5-15%</td> </tr> <tr> <td>OTHERS</td> <td style="text-align: right;">2-5%</td> </tr> </tbody> </table> | Components | % Range | RESIN | 20-45% | EVA | 45-70% | MICRO WAX | 5-15% | OTHERS | 2-5% |
| Components | % Range | | | | | | | | | | |
| RESIN | 20-45% | | | | | | | | | | |
| EVA | 45-70% | | | | | | | | | | |
| MICRO WAX | 5-15% | | | | | | | | | | |
| OTHERS | 2-5% | | | | | | | | | | |
| <p>3. Data on product safety</p> | <p>Our product has no dangerous for person.</p> | | | | | | | | | | |
| <p>4. First aid hints Skin scald</p> | <p>If you scalded careless during operating procedure, wash you skin with plenty of water.</p> | | | | | | | | | | |
| <p>5. Fire protection Fire risks</p> | <p>Keep away from heat and flame. Therefore the storage must follow general fire protection regulations.</p> | | | | | | | | | | |
| <p>6. Measures to be taken in the case of an accidental leak</p> | <p>The breakage of products also has no dangerous for people.</p> | | | | | | | | | | |
| <p>7. Handling and storage Hints for handling Hints for storage</p> | <p>Keep to local regulations and instructions for the safety of work in the course of handling. Store in dry and shady rooms. Keep away from light. Guarantee period is 1 year.</p> | | | | | | | | | | |
| <p>8. Check for exposure and personnel protection Check for exposure effect Personal protection</p> | <p>In the sun ,the product will change color(from white to yellow).But the quality is not change. Also that's not dangerous for people.</p> | | | | | | | | | | |
| <p>9. Physical and chemical properties appearance</p> | <p>transparent 10000 ±1000mpa.s(180℃) CPS</p> | | | | | | | | | | |

| | |
|--|--|
| viscosity (180°C) Softening point | 80±2°C |
| 10. Stability and reactivity Conditions of product stability Dangerous destructive products | Supplied in stable form. No dangerous |
| 11. Toxicological information | The products ready for minimum danger to human health excepting the risks described above. |
| 12. Ecological information | Hot melt sticks are glue which is environmentally friendly |
| 13. Information on disposal | absence |
| 14. Forwarding information | The products should be protected against long-lasting exposure to humidity, rain, snow, and frost. |
| 15. Legal regulations | absence |
| 16. Further information | The above information describes is based on the current state of our knowledge. |